

## PONY PUMP® SERIES - 1/10 HP

### APPLICATIONS

Commercial, industrial, and home uses where liquid must be transferred

### FEATURES

- Self-priming for instant delivery or dewatering up to 6 ft (1.8 m)
- Non-submersible stainless steel or plated brass pump body
- Rugged metallic handle for easy portability
- Dual threaded intake and discharge with both 3/4" male garden hose thread and 3/8" FNPT
- Model 360K includes pump, hose, strainer, and suction adapter
- Separate kit options available
- Includes 2 extra impellers and gasket
- Model 365 and 365S include 6 ft (1.8 m) lead wires with battery alligator clips
- Models 360 and 365 have a nitrile shaft seal
- Model 370 has a fluoroelastomer shaft seal for improved temperature and abrasion resistance



### SERIES SPECIFICATIONS

Volts	Hz	Amps		Watts	Gallons per hour (Liters per hour) @ Height				Shut-Off	PSI
		FLA	Start		1'	5'	10'	20'		
115	60	1.6	2.4	91	360 (1362.74)	330 (1249.19)	300 (1135.62)	250 (946.35)	25' (7.62 m)	10.8
12 VDC	-	7	14	84	300 (1135.62)	270 (1022.06)	240 (908.5)	202 (746.65)	25' (7.62 m)	10.8

Item No.	Model	HP	Volts	Material	Operation	Cord	Weight lbs (kg)
555112	360	1/10	115	Plated Brass	Self-Priming	6' (1.8 m)	3.4 (1.54 Kg)
555110	360S	1/10	115	Stainless Steel	Self-Priming	6' (1.8 m)	3.4 (1.54 Kg)
555113	370	1/10	115	Plated Brass	Self-Priming	6' (1.8 m)	4.7 (2.12 Kg)
555602	365	1/10	12 VDC	Plated Brass	Self-Priming	6' Leads w/clips (1.8 m)	4.7 (2.12 Kg)
555606	365K	1/10	12VDC	Plated Brass	Self-Priming	6' Leads w/clips (1.8 m)	7.0 (3.2 Kg)
555203	365S	1/10	12 VDC	Stainless Steel	Self-Priming	6' Leads w/clips (1.8 m)	4.7 (2.12 Kg)
555111	360K	1/10	115	Plated Brass	Self-Priming	6' (1.8 m)	8.0 (3.6 Kg)